



RAVENOL Getriebeöl SLG SAE 80W-90

RAVENOL SLG SAE 80W-90 Gear Oil is a high performance multi-purpose gear oil primarily developed for commercial vehicle transmissions. It is produced from selected base oils together with specially designed additives to offer excellent pumpability at low temperatures and high lubrication protection at high temperatures.

Application Notes

RAVENOL SLG SAE 80W-90 Gear Oil is a multi-purpose gear oil for universal use in commercial vehicle transmissions, rear axles and auxiliary drives, including highly stressed hypoid-drive axles.

Quality Classifications

Specifications

API GL-5, API GL-4, MT-1, MIL-L-2105 A/B/C/D/E

Approvals

MAN 341 Typ E2

Practice and tested in aggregates with filling

MAN 3343 Typ M (prolonged Oil drain intervals), ZF-TE-ML 02B, 05A, 12E, 16B, 17B, 19B, 21A, SCANIA STO 1:0, VOLVO 97310

Characteristic

RAVENOL Getriebeöl SLG SAE 80W-90 offers:

- Excellent thermal stability.
- Exceptional EP properties.
- A good cold flow behaviour at low temperatures.
- Extended service life potential.
- Compatible with all types of sealing materials.
- Reliable protection against wear, sludge, adhesives & corrosion.

Characteristics	Unit	Data	Audit
Colour		braun	visual
Density at 20°C	kg/m ³	889	EN ISO 12185
Viscosity at 40°C	mm ² /s	146,4	DIN 51 562
Viscosity at 100°C	mm ² /s	15,2	DIN 51 562
Viscosity index VI		105	DIN ISO 2909
Flash point (COC)	°C	168	DIN ISO 2592
Pourpoint	°C	-27	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

11.05.2015

Ravensberger Schmierstoffvertrieb GmbH

Postfach 1163

33819 Werther

Tel.: 05203/9719-0

Fax.: 052039719-40 / 41