

RAVENOL SNOWMOBILES Teilsynth. 2-Takt

RAVENOL SNOWMOBILES Teils ynth. 2-Takt is high quality 2-stroke engine oil with special esters and Polyisobutylene (PIB) based on high quality base oils with an ash less additive package for optimum lubricity and excellent corrosion protection.

Application Notes

RAVENOL SNOWMOBILES Teilsynth. 2-Takt is recommended for typical mixing ratio: 1: 75

RAVENOL SNOWMOBILES Teilsynth. 2-Takt is particularly suitable for the lubrication of air-cooled two-stroke gasoline engines with high speed and heavy load. RAVENOL SNOWMOBILES Teilsynth. 2-Takt is ideal for lubricating two-stroke snowmobiles with suitable water cooling.

Quality Classifications

RAVENOL SNOWMOBILES Teilsynth. 2-Takt is approved and corresponds to the following specifications:

Specifications

APITC, ISO-L-EGC

Approvals

JASO 049RAV152

Practice and tested in aggregates with filling

Suzuki, Yamaha, Kawasaki, Arctic Cat, Bombardier, Ski-Doo, Polaris

Characteristic

RAVENOL SNOWMOBILES Teilsynth. 2-Takt offers:

- proper lubrication of all engine parts
- a strong cleaning effect, the combustion chambers and inlet and outlet ports freeing up largely of combustion residues and deposits
- contains additives, designed on clean spark plugs ensure optimal performance of the engines
- an excellent corrosion
- a very high wear and corrosion protection
- low exhaust emissions through good combustion

Characteristics	Unit	Data	Audit	
Colour		blue	visual	_
Density at 15°C	kg/m³	0,871	EN ISO 12185	
Density at 20°C	kg/m³	0,868	EN ISO 12185	
Viscosity at 40°C	mm²/s	35,9	DIN 51 562	
Viscosity at 100°C	mm²/s	6,29	DIN 51 562	
Viscosity index VI		126	DIN ISO 2909	
Pourpoint	°C	-30	DIN ISO 3016	

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

13.01.2016

Ravensberger Schmierstoffvertrieb GmbH Postfach 1163 33819 Werther

Tel.: 05203/9719-0 Fax.: 052039719-40 / 41